



CorePro LEDlinear MV



CorePro LED linear R7S 118mm 7.2-60W 830

CorePro R7S is a retrofit replacement for traditional double-ended linear R7S lamps. Its 'light all around' design delivers light just like a halogen lamp. Within the range you can choose dimmable products which have deep dimming function that enables a cozy ambience when using a dimmable fixture.

Product data

General information		Warm Up Time to 60% Light (Nom)	
Cap-Base	R7S [R7s]	Power Factor (Nom)	0.5
EU RoHS compliant	Yes	Voltage (Nom)	220-240 V
Nominal Lifetime (Nom)	15000 h	Temperature	
Switching Cycle	8000X	T-Case Maximum (Nom)	110 °C
Flux measurement reference	Sphere	Controls and dimming	
Light technical		Dimmable	No
Color Code	830 [CCT of 3000K]	Mechanical and housing	
Luminous Flux (Nom)	810 lm	Bulb Finish	Clear
Color Designation	White (WH)	Bulb Shape	Linear
Correlated Color Temperature (Nom)	3000 K	Approval and application	
Luminous Efficacy (rated) (Nom)	112.00 lm/W	Energy Efficiency Class	E
Color Consistency	<6	Suitable For Accent Lighting	No
Color Rendering Index (Nom)	80	Energy Consumption kWh/1000 h	8 kWh
LLMF At End Of Nominal Lifetime (Nom)	70 %	EPREL Registration Number	624213
Operating and electrical		Product data	
Input Frequency	50 to 60 Hz	Full product code	871951430397300
Power (Nom)	7.2 W	Order product name	CorePro LED linear R7S 118mm 7.2-60W 830
Lamp Current (Nom)	40 mA		
Wattage Equivalent	60 W		
Starting Time (Nom)	0.5 s		

CorePro LEDlinear MV

EAN/UPC - Product	8719514303973
Order code	929002495002
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10

Material Nr. (12NC)	929002495002
Net Weight (Piece)	0.016 kg



Dimensional drawing



Product	D	C
CorePro LED linear R7S 118mm 7.2-60W 830	15 mm	118 mm


CorePro LED linear R7S 118mm 7.2-60W 830

Photometric data



LEDlinear CorePro 7,2W R7S 830-LDD

LEDlinear CorePro 7,2W R7S 830-POC



© 2022 Philips Lighting B.V. Page 11

LEDlinear CorePro 7,2W R7S 830-GUL

CorePro LEDlinear MV

Lifetime



15K LED

15K LMP

