



- Hybrid AHD DVR
- 4-channel
- AHD/TVI/CVI/CVBS/IP support
- 5.0Mp AHD support
- 1xSATA (max. 8Tb)
- ONVIF 2.4 protocol support
- Support mobile monitoring:
iOS & Android
- Ability to work with Partizan
Cloud Storage
- Remote access to the device
with Partizan MAC

Your manual is here:
<http://manuals.partizan.global>



Partizan software:
<http://apps.partizan.global>



System		
Model	ADM-44U	
Version	FullHD v5.1	
Maximum connected cameras, pcs.	4	
Operating system	Embedded Linux	
Simultaneous multi-channel real-time recording	+	
Playback	+	
Network operation	+	
USB backup	+	
Operation modes	AHD/TVI/CVI/CVBS/IP	
Record		
Record, channels x resolution @ fps	AHD	4x5M-N@12, 4xAHD-H@15
	AHD + IP	2xAHD-H@25+2x1080p@25, 4xAHD-M@25+4x960p@25
	IP	16x1080p@25, 16x960p@25, 4x5.0Mp@25
Record storage, HDD*/network		+/+
Video compression		H.264
Space occupation for 25 fps/1 channel (per day)	Video	~80Gb(1080p), ~46Gb(960p), ~34Gb(720p), ~30Gb(960H), ~20Gb(D1)
	Audio	0.69Gb
*Please note, HDD is not included in the kit!		
Playback		
Playback archive records, channels x resolution @ fps	AHD	4x5M-N@12, 4xAHD-H@12
	AHD + IP	2xAHD-H@25, 2x1080p@25, 4xAHD-M@25, 4x960p@25
	IP	2x1080p@25, 4x960p@25, 1x5.0Mp@25
Backup mode, network/USB		+/+
Preview screen		1/4
Record mode	Manual	+
	Alarm	+
	Motion Detection	+
	Schedule	+
Audio		
Audio compression		G.711A
Two-way audio		+
Network		
Network Interface		RJ-45 (10/100Base-T)
Network functions		NiP/DDNS/IPFilter>Email/NTP/UPNP/FTP/RTSP
Languages supported		English, Russian, Arabic, French, Polish, Romanian, Hungarian, Italian, Czech
Default IP address		DHCP (Auto)
Default username		admin
Default password		admin
HTTP port		80
RTSP port		554
RTSP string		rtsp://192.168.1.10:554/user=admin&password=admin&channel=1&stream=0.sdp?
Control port		34567
Configuration software		Partizan (Setup Tool), Partizan Device Manager
Monitoring program		Partizan, Partizan CMS, Partizan VMS
Mobile software (support)		Partizan
Protocol integration		Partizan SDK, ONVIF 2.4+
Interface		
Display quality		1920x1080; 1440x900; 1280x1024; 1280x720; 1024x768
Video	Inputs	4ch BNC
	Outputs	1ch VGA, 1ch HDMI
Audio	Inputs	1ch RCA
	Outputs	1ch RCA
Alarm	Inputs	-
	Outputs	-
PTZ control, port/protocol support		-
USB		2xUSB2.0
Internal SATA, pcs x max.Tb		1x8
External SATA, pcs x max.Tb		-
External eSATA, pcs x max.Tb		-
Dimensions		
Size, mm		210x200x49
Weight, g		900
Common		
Accessories	Optical mouse	+
	Power adapter	+
	IR remote	-
Power supply	DC12V, A	2.0
	PoE/Class	-
Housing material, plastic/metal		+-
Front material, plastic/metal		+-
Operating temperature, °C		0 - +55
Warranty, years		3