

# PRODUCT CARD



PRODUCT CODE: AD-NL-6148WLR4

EAN CODE: 5908254817489

## TOS LED 30W garden floodlight with PIR, 2200lm, IP65, 4000K, PC, white

Garden floodlight intended for outdoor installation, as parking and garden lighting, or to provide light to building facades, advertisements, etc. It can also be used indoors, e.g. in garages, halls. Its simple shape and wide lampshade without any frame, make the floodlight look good on buildings decorated in various styles. The light source in form of SMD LED diodes, guarantee high energy efficiency and long life of the device. Rated power of the presented floodlight is 30W and it emits light with the luminous flux of 2200 lm. It shines with a natural white color, with a temperature of 4000K. The device has a built-in PIR sensor that turns on the light only when movement is detected and allows to set the lighting time according to individual preferences (from 10 +/- seconds to 15 +/- minutes). The sensor detects movement both during the day and at night. The maximum detection range is 10 meters. The movable housing allows to adjust the lighting angle to the room conditions (horizontally 180°, vertically 125°). High degree of ingress protection IP65 protects the floodlight against the ingress of water, dust and dirt, which is why this product will withstand even the most difficult weather conditions (-20 ~ +40 °C). Available colors: white or black.



**Light source:**  
LED SMD



**Degree of protection (IP):**  
65




**Adjustable time setting (TIME):**



**Rated power:**  
30W



**Detection angle:**  
240°



**Colour temperature:**  
4000K



**Control of the motion sensor:**

## General information

**Light source:** LED SMD

**Rated power:** 30 W

**Nominal voltage:** 230V~, 50Hz

**Luminous flux:** 2200 lm

**Colour:** white

**Solar panel:** no

**Colour temperature:** 4000K

**Degree of protection (IP):** 65

**Colour rendering index CRI:** >80

**Detection angle:** 240°

**Dimensions - depth:** 199 mm

**Dimensions - height:** 187 mm

**Material of the lampshade:** PC

**Control of the motion sensor:** yes

**Type of sensor:**

**Detection range:** 5-10 m

**Daylight sensor adjustment range (LUX):** <3—2000lux

**Adjustable time setting (TIME):** yes

**Lighting time adjustment range (TIME):** min.: 10 sek. ± 3 sek., max.: 15min.±2min

**Adjustment of motion detection range (SENS):** yes