


## CABLE SPECIFICATION

### FX/ISP2-LSZH-GRY (8723)

Audio, Control & Instrument Cable, 22 AWG stranded (7x24mm) tinned copper conductors, polypropylene insulation, twisted pairs, individually shielded (100% coverage), 24 AWG stranded tinned copper drain wire, LSZH jacket.

#### GENERAL

Inner Conductor	22AWG Stranded tinned copper
Insulation	PE
Pairs	2
Pairs Insulation Color	Black, Red, White, Green
Individually Pair Foil	AL/PET
Drain Wire	24AWG Stranded tinned copper
Rip Cord	Yes White
Jacket	Grey (RAL7042) LSZH



#### DIMENSIONS – (mm)

2 Pairs Conductor diameter	7*0.24
2 Pairs Isolation diameter	1.20
Nom. Thickness	0.24
Drain Wire	7*0.19
Diameter	4.30
Nom. Thickness	0.55

#### ELECTRICAL CHARACTERISTICS

Rated Voltage	600V
Max. Recommended Current [A]	2.3 Amps per conductor @ 25°C
Conductor DCR	56.0 Ohm/Km
Individual Pair Nominal Shield DCR	68 Ohm/Km
Rated Temperature	-40°C - 70°C
Packing	100M Carboard reel, 6 reels per Outer box, 48 boxes per pallet

#### PACKING

100M Carboard reel	180*75*110
100M Outer box	550*370*120
100M Pallet	1120*1120
Pallet label	290*210
Print Height	2.50 ± 0.50

#### NOTES:

1. CABLE PRINT: FOTUX ISP2 2x2x22AWG 600V Individually Screened LSZH RoHS2 xxxxm  
Repeat every meter replacing xxx with meter counts up from 001 to 100,200,500,1000 then reset to repeat starting from 001 again.
2. The test report is required to cover all the test items which are listed in above.
3. Cable and packaging must be RoHS compliant.
4. Cable must be CPR Class Eca compliant.