

PRODUCT FAMILY DATASHEET LEDVANCE OUTDOOR LED FACADE LANTERN

Contemporary lanterns with light guide for low-glare illumination



AREAS OF APPLICATION

- Outdoor
- Building facades
- Gardens, balconies and other outdoor areas

PRODUCT BENEFITS

- Energy-efficient thanks to LED technology
- 5 years guarantee
- Easy and quick installation
- Special light guide design for low-glare illumination

PRODUCT FEATURES

- Bright and functional outdoor LED luminaires
- Type of protection: IP54
- Die-cast aluminum housing
- Diffuser made of opal polycarbonate with transparent polycarbonate cover





	Electrical data						Photometri cal data	Light technical data	Dimensions & we	eight	
Product description	Operating mode	Mains	Power factor λ	Nominal	Nominal	Nominal	Luminous	Beam	Length	Width	Height
		frequency		wattage	voltage	current	flux	angle			
LED FACADE LANTERN 12 W 3000 K GY ¹⁾	Mains voltage	50/60 Hz	>0.5	12.00 W	220240 V	0.096 A	610 lm	210.00°	176.0 mm	110.0 mm	240.0 mm

	Colors & materials	Temperatures & operating conditions	Additional product data	Capabilities		Certificates & standards		
Product description	Product color	Ambient temperature range	Mounting location	Type of connection	LED module replaceable	Dimmable	Type of protection	Protection class
LED FACADE LANTERN 12 W 3000 K	Gray	-2040 °C	Wall	Terminal, 3-Pole (L, N, PE)	Not replaceable	No	IP54	1

Product description	Protection class IK (shock resistance)	Photobiological safety group	Standards
LED FACADE LANTERN 12 W 3000 K GY ¹⁾	IK06	RG 0	CE

¹⁾ Available from February 2018





LED FACADE LANTERN 12 W 3000 K GY

LED FACADE LANTERN 12 W 3000 K GY

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075074835	LED FACADE LANTERN 12 W 3000 K GY	Shipping carton box 4	425 mm x 285 mm x 315 mm	38.15 dm³	5822.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see

www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.