

PRODUCT FAMILY DATASHEET LEDVANCE OUTDOOR LED SURFACE POLE

Stainless steel surface-luminaires with indirect illumination



AREAS OF APPLICATION

- Outdoor
- Building facades
- Decorative illumination

PRODUCT BENEFITS

- Energy-efficient thanks to LED technology
- 5 years guarantee
- Easy and quick installation
- Special light guide design for low-glare illumination

PRODUCT FEATURES

- Bright and functional outdoor LED luminaires
- Type of protection: IP44
- Housing made of Polycarbonate covered with stainless steel
- Available as wall, ceiling and bollard luminares
- Diffuser made of transparent polycarbonate




TECHNICAL DATA


	Electrical data						Photometri cal data	Light technical data	Dimensions a	& weight	Colors & materials
Product description	Operating mode	Mains frequency	Power factor λ	Nominal wattage	Nominal voltage	Nominal current	Luminous flux	Beam angle	Diameter	Height	Product color
LED SURFACE POLE 6 W 3000 K SST	Mains voltage	50/60 Hz	>0.5	6.00 W	220240 V	0.06 A	360 lm	160 °	102.0 mm	87.0 mm	Steel

	Temperatures & operating conditions	Lifespan	Additional product data	Capabilities			Certificates & standards
Product description	Ambient temperature range	Lifespan L70 at 25 °C	Mounting location	Type of connection	LED module replaceable	Dimmable	Type of protection
LED SURFACE POLE 6 W 3000 K SST	-2040 °C	30000 h	Ceiling / Wall	Terminal, 2-Pole (L, N)	Not replaceable	No	IP44

Product description		Protection class	Protection class IK (shock resistance)	Photobiological safety group	Standards
LED SURFACE POLE 6	W 3000 K SST	11	IK06	RG 0	CE

¹⁾ Available from February 2018





LED SURFACE POLE 6 W 3000 K SST

LED SURFACE POLE 6 W 3000 K SST

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075075177	LED SURFACE POLE 6 W 3000 K SST	Shipping carton box 6	380 mm x 175 mm x 320 mm	21.28 dm³	2091.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see

www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.