

LEVANTO UGR LED1X3650 G673 T840 MPRZ • 1109030



Product:	Levanto UGR LED1x3650 G673 T840 MPRZ
Order code:	1109030
Family:	Levanto UGR LED
Product group:	Recessed luminaires

GENERAL DATA

Description:	Recessed mounted LED panel Light distribution type: direct Optical system: micro-prismatic diffuser, UGR<19 Housing: aluminum Colour: white (RAL9016)
Installation:	In modular suspended ceilings (600x600), in ceilings with cut-out openings (accessories to be ordered separately). Push-in terminal, 2x1x1.5mm2
Environment	Indoor
Application	office, education, corridor, retail, public place

ELECTRICAL DATA

Mains voltage:	220-240V, 50/60Hz	System power*, W:	36
Power factor:	>0,9	Control gear:	ECG on/off
Integrated sensor:	None	Connection:	Push-in terminal, 2x1x1.5mm2

LIGHTING DATA

Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm(ta+25°C):	3650	System efficacy, lm/W:	100
CRI (Ra):	80+	CCT, K:	4000
SDCM:	5	Light Distribution:	Symmetrical wide beam (76 ...125)
Distribution Type:	Direct	Beam angle, °:	90
UGR index:	≤19	LED lifetime, h:	50000/L70B50


TECHNICAL DATA

Net weight, kg:	1.8	Quantity in package, pcs:	1
Packaging volume, m3/pcs:	0.0175	Pallet quantity, pcs:	96
Dimensions, mm:	595x595x33		


STANDARDS

Operating temperature range, °C:	ta 0...+35	Protection class IEC:	II
Ingress protection code:	IP40	Mechanical impact resistance:	IK02
EEC:	E	Certificates:	CE, UKCA, RoHS
Warranty:	3 years (5 years - see warranty Ts and Cs)		

Technical drawing (.jpg)



Light distribution curve (.jpg)



Note:

Tolerance range for optical and electrical data: $\pm 10\%$. Values apply to an ambient temperature of 25 C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification. Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.