

PRODUCT DATASHEETLED FACADE BELT 11 W 3000 K RD GY

LEDVANCE OUTDOOR LED FACADE BELT | Luminaires with modern design and light outlet up and down



AREAS OF APPLICATION

- Outdoor
- Building facades
- Entrance lighting

PRODUCT BENEFITS

- Energy-efficient thanks to LED technology
- 5 years guarantee
- Easy and quick installation
- Homogeneous light output

PRODUCT FEATURES

- Bright and functional outdoor LED luminaires
- Type of protection: IP54
- Die-cast aluminum housing
- Available in round and square form
- Diffuser made of opal PMMA



TECHNICAL DATA

Electrical data

| Operating mode | Mains voltage |
|-----------------|---------------|
| Mains frequency | 50/60 Hz |
| Power factor λ | >0.5 |
| Nominal wattage | 11.00 W |
| Nominal voltage | 220240 V |
| Nominal current | 0.057 A |


Photometrical data

| Luminous efficacy | 35 lm/W |
|--------------------------------------|------------|
| Luminous flux | 400 lm |
| Color temperature | 3000 K |
| Light color (designation) | Warm White |
| Color rendering index Ra | ≥80 |
| Standard deviation of color matching | <6 sdcm |

Light technical data

| Peam angle | 335.00 ° |
|------------|----------|
| Beam angle | 333.00 |
| | |

Dimensions & weight



| Length | 60.0 mm |
|----------------|----------|
| Width | 240.0 mm |
| Height | 142.0 mm |
| Product weight | 720.00 g |

Colors & materials

| Housing color | Gray |
|---------------|------|
| Product color | Gray |

| Body material | Aluminum | |
|----------------|-------------------------------|--|
| Cover material | Polymethylmethacrylate (PMMA) | |

Temperatures & operating conditions

| Temperature range in operation | -2040 °C |
|--------------------------------|----------|
| Ambient temperature range | -2040 °C |

Lifespan

| Number of switching cycles | 15000 |
|----------------------------|---------|
| Lifespan L70 at 25 °C | 30000 h |

Additional product data

| Mounting location | Wall | |
|-------------------|------------------------------|--|
| Product remark | Available from February 2018 | |

Capabilities

| Type of connection Terminal, 3-Pole (L, N, PE) | | |
|--|-----------------|--|
| Dimmable | No | |
| LED module replaceable | Not replaceable | |

Certificates & standards

| Type of protection | IP54 |
|--|------|
| Protection class | 1 |
| Protection class IK (shock resistance) | IK06 |
| Photobiological safety group | RG 0 |
| Standards | CE |

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

LOGISTICAL DATA

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|--------------------------------------|---------------------------------|--------------------------------------|-----------|--------------|
| 4058075074972 | LED FACADE BELT 11 W 3000 K RD GY | Shipping carton box 6 | 600 mm x 220 mm x 290 mm | 38.28 dm³ | 5616.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see

www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.