

PRODUCT DATASHEET

LED FACADE UPDOWN 12 W 3000 K WT

LEDVANCE OUTDOOR LED FACADE UPDOWN | Luminaires with classic shape and light outlet up and down



AREAS OF APPLICATION

- Outdoor
- Building facades
- Decorative illumination

PRODUCT BENEFITS

- Energy-efficient thanks to LED technology
- 5 years guarantee
- Easy and quick installation
- Homogeneous light output

PRODUCT FEATURES

- Very bright and functional outdoor LED luminaires
- Type of protection: IP54
- Die-cast aluminum housing
- Available in two housing colors: white and dark gray
- Diffuser made of clear glass



TECHNICAL DATA

Electrical data

Operating mode	Mains voltage
Mains frequency	50/60 Hz
Power factor λ	>0.5
Nominal wattage	12.00 W
Nominal voltage	220...240 V
Nominal current	0.055 A


Photometrical data

Luminous efficacy	60 lm/W
Luminous flux	710 lm
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	≥ 80
Standard deviation of color matching	<6 sdc _m

Light technical data

Beam angle	280.00 °
-------------------	----------

Dimensions & weight



Length	55.0 mm
Width	90.0 mm
Height	160.0 mm
Product weight	480.00 g

Colors & materials

Housing color	White
Product color	White

Body material	Aluminum
Cover material	Glass

Temperatures & operating conditions

Temperature range in operation	-20...40 °C
Ambient temperature range	-20...40 °C

Lifespan

Number of switching cycles	15000
Lifespan L70 at 25 °C	30000 h

Additional product data

Mounting location	Wall
Product remark	Available from February 2018


Capabilities

Type of connection	Terminal, 3-Pole (L, N, PE)
Dimmable	No
LED module replaceable	Not replaceable

Certificates & standards

Type of protection	IP54
Protection class	I
Protection class IK (shock resistance)	IK06
Photobiological safety group	RG 0
Standards	CE

Light Distribution



LDC typ polar

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075075078	LED FACADE UPDOWN 12 W 3000 K WT	Shipping carton box 6	245 mm x 240 mm x 195 mm	11.47 dm ³	3193.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see
 ▶ www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.